

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : 0075W-A
Product code : 0075W-A
Other means of identification : 0075W-A/5SF, 0075W-A/5, 0075W-A/55

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Protective Industrial Polymers
7875 Bliss Parkway
North Ridgeville, Ohio 44039 - USA-Ohio
T 440-327-0015
www.protectpoly.com

1.4. Emergency telephone number

Emergency number : Chemtrec: 800-424-9300 (Outside USA) 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 1A	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization Category 1	H317	May cause an allergic skin reaction
Hazardous to the aquatic environment - Acute Hazard Category 2	H401	Toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411	Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :

- H302 - Harmful if swallowed
- H314 - Causes severe skin burns and eye damage
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H401 - Toxic to aquatic life
- H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

- P260 - Do not breathe dust
- P261 - Avoid breathing vapors
- P264 - Wash hands, forearms and face thoroughly after handling
- P270 - Do not eat, drink or smoke when using this product
- P272 - Contaminated work clothing must not be allowed out of the workplace
- P273 - Avoid release to the environment
- P280 - Wear protective clothing
- P301+P312 - If swallowed: Call a doctor if symptoms persist. if you feel unwell

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P302+P352 - If on skin: Wash with plenty of soap
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a doctor if symptoms persist.
P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)
P330 - Rinse mouth
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P363 - Wash contaminated clothing before reuse
P391 - Collect spillage
P405 - Store locked up
P501 - Dispose of contents/container to in accordance with local regulations

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer	(CAS No) 25085-99-8	65 - 70	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317
Phenol,4-nonyl-,branched	(CAS No) 84852-15-3	19 - 25	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Benzenemethanol	(CAS No) 100-51-6	< 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
silicon dioxide, amorphous	(CAS No) 112945-52-5	0 - 5	Not classified
Distillates (petroleum), hydrotreated middle	(CAS No) 64742-46-7	0.3 - 1	Asp. Tox. 1, H304
Propane-1,2,3-triol	(CAS No) 56-81-5	< 1	Not classified
Solvent naphtha (petroleum), light aromatic	(CAS No) 64742-95-6	0.105 - 0.6	Flam. Liq. 2, H225 Resp. Sens. 1B, H334
1-methoxy-2-propyl acetate	(CAS No) 108-65-6	0.0175 - 0.1	Flam. Liq. 3, H226
Octamethylcyclotetrasiloxane	(CAS No) 556-67-2	0.00005 - 0.001	Flam. Liq. 3, H226

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing vapors.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing vapors.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-, homopolymer (25085-99-8)

Not applicable

Phenol, 4-nonyl-, branched (84852-15-3)

Not applicable

Benzenemethanol (100-51-6)

Not applicable

1-methoxy-2-propyl acetate (108-65-6)

Not applicable

Solvent naphtha (petroleum), light aromatic (64742-95-6)

Not applicable

Octamethylcyclotetrasiloxane (556-67-2)

Not applicable

Distillates (petroleum), hydrotreated middle (64742-46-7)

Not applicable

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

silicon dioxide, amorphous (112945-52-5)		
Not applicable		
Propane-1,2,3-triol (56-81-5)		
ACGIH	Local name	Glycerin mist
ACGIH	Remark (ACGIH)	URT irr

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following colour(s): Colourless or yellow Light yellow Colourless Colourless to white
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Mild odour Phenol odour Fruity odour Aromatic odour Ether-like odour Odourless
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 608 °F
Flash point	: 514 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

0075W-A	
ATE US (oral)	500 mg/kg body weight
Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-, homopolymer (25085-99-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
Phenol,4-nonyl-,branched (84852-15-3)	
LD50 oral rat	1412 mg/kg body weight (Other, Rat, Male / female, Experimental value, Oral)
ATE US (oral)	1412 mg/kg body weight
Benzenemethanol (100-51-6)	
LD50 oral rat	1620 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 inhalation rat (mg/l)	> 4.178 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
ATE US (oral)	1620 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
1-methoxy-2-propyl acetate (108-65-6)	
LD50 oral rat	6190 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	> 5000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male / female, Experimental value, Dermal)
ATE US (oral)	6190 mg/kg body weight
Octamethylcyclotetrasiloxane (556-67-2)	
LD50 oral rat	> 4800 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2400 mg/kg body weight (Equivalent or similar to OECD 402, Rat, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	36 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
ATE US (vapors)	36 mg/l/4h
ATE US (dust, mist)	36 mg/l/4h
silicon dioxide, amorphous (112945-52-5)	
LD50 oral rat	> 10000 mg/kg (Rat, Oral)

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

silicon dioxide, amorphous (112945-52-5)	
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Dermal)
Propane-1,2,3-triol (56-81-5)	
LD50 oral rat	27200 mg/kg (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral)
LC50 inhalation rat (mg/l)	> 2.75 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Converted value, Inhalation (vapours))
ATE US (oral)	27200 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

Phenol,4-nonyl-,branched (84852-15-3)	
LC50 fish 1	0.08 mg/l (ASTM E729-96, 96 h, Hybopsis monacha, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	0.084 mg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value)

Benzenemethanol (100-51-6)	
LC50 fish 1	460 mg/l (EPA OPP 72-1, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	230 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Fresh water, Experimental value, GLP)
ErC50 (algae)	770 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

1-methoxy-2-propyl acetate (108-65-6)	
LC50 fish 1	100 - 180 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	> 500 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)

Octamethylcyclotetrasiloxane (556-67-2)	
LC50 fish 1	> 0.022 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	> 0.015 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, GLP)

silicon dioxide, amorphous (112945-52-5)	
LC50 fish 1	> 10000 mg/l (96 h, Brachydanio rerio, Literature)
EC50 Daphnia 1	> 10000 mg/l (24 h, Daphnia magna, Literature)

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propane-1,2,3-triol (56-81-5)	
LC50 fish 1	54000 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Lethal)
EC50 Daphnia 1	> 10000 mg/l (24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)

12.2. Persistence and degradability

Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-, homopolymer (25085-99-8)	
Persistence and degradability	Not readily biodegradable in water.

Phenol,4-nonyl-,branched (84852-15-3)	
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.

Benzenemethanol (100-51-6)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance

1-methoxy-2-propyl acetate (108-65-6)	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.

Octamethylcyclotetrasiloxane (556-67-2)	
Persistence and degradability	Not readily biodegradable in water.

silicon dioxide, amorphous (112945-52-5)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

Propane-1,2,3-triol (56-81-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.87 g O ₂ /g substance
Chemical oxygen demand (COD)	1.16 g O ₂ /g substance
ThOD	1.217 g O ₂ /g substance
BOD (% of ThOD)	0.71

12.3. Bioaccumulative potential

Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-, homopolymer (25085-99-8)	
Log Pow	3.242 (Literature)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Phenol,4-nonyl-,branched (84852-15-3)	
BCF fish 1	1200 - 1300 (OECD 305: Bioconcentration: Flow-Through Fish Test, 16 day(s), Gasterosteus aculeatus, Flow-through system, Salt water, Experimental value, Fresh weight)
Log Pow	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

Benzenemethanol (100-51-6)	
Log Pow	1 - 1.1 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

1-methoxy-2-propyl acetate (108-65-6)	
Log Pow	1.2 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Solvent naphtha (petroleum), light aromatic (64742-95-6)	
Log Pow	2.1 - 6

Octamethylcyclotetrasiloxane (556-67-2)	
BCF fish 1	12400 (Other, 672 h, Pimephales promelas, Flow-through system, Experimental value, GLP)

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Octamethylcyclotetrasiloxane (556-67-2)	
Log Pow	4.45 - 5.1 (Literature)
Bioaccumulative potential	High potential for bioaccumulation (BCF > 5000).
silicon dioxide, amorphous (112945-52-5)	
Bioaccumulative potential	Not bioaccumulative.
Propane-1,2,3-triol (56-81-5)	
Log Pow	-1.75 (Experimental value, Equivalent or similar to OECD 107, 25 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer (25085-99-8)	
Ecology - soil	Low potential for mobility in soil.
Phenol,4-nonyl-,branched (84852-15-3)	
Log Koc	4.35 - 5.69 (log Koc, Other, Experimental value, GLP)
Ecology - soil	Adsorbs into the soil.
Benzenemethanol (100-51-6)	
Surface tension	39 mN/m (20 °C)
Ecology - soil	No (test)data on mobility of the substance available.
1-methoxy-2-propyl acetate (108-65-6)	
Surface tension	29.4 mN/m (20 °C, 100 vol %, EU Method A.5: Surface tension)
Log Koc	0.264 (log Koc, QSAR)
Ecology - soil	Highly mobile in soil.
Octamethylcyclotetrasiloxane (556-67-2)	
Log Koc	4.22 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Experimental value, GLP)
Ecology - soil	Low potential for mobility in soil.
silicon dioxide, amorphous (112945-52-5)	
Ecology - soil	No (test)data on mobility of the substance available.
Propane-1,2,3-triol (56-81-5)	
Surface tension	0.0634 N/m (20 °C, 1000 g/l)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. (Phenol,4-nonyl-,branched,Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer), 8, III

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.
Phenol,4-nonyl-,branched,Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : III - Minor Danger

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 8 - Corrosive



Dangerous for the environment : Yes

Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Emergency Response Guide (ERG) Number : 154

Other information : No supplementary information available.

TDG

Not applicable

Transport by sea

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III

UN-No. (IMDG) : 3082

Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Class (IMDG) : 9 - Miscellaneous dangerous compounds

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Marine pollutant : Yes



Air transport

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IATA)	: 3082
Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s.
Class (IATA)	: 9 - Miscellaneous Dangerous Goods
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

0075W-A

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

silicon dioxide, amorphous	CAS No 112945-52-5	0 - 5%
----------------------------	--------------------	--------

Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer (25085-99-8)

EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
--------------------------	---

Phenol,4-nonyl-,branched (84852-15-3)

Subject to reporting requirements of United States SARA Section 313

1-methoxy-2-propyl acetate (108-65-6)

EPA TSCA Regulatory Flag	P - P - indicates a commenced PMN substance.
--------------------------	--

15.2. International regulations

CANADA

Oxirane, 2,2'-(1-methylethylidene)bis(4,1[4-phenyleneoxymethylene])bis-,homopolymer (25085-99-8)

Listed on the Canadian DSL (Domestic Substances List)

Phenol,4-nonyl-,branched (84852-15-3)

Listed on the Canadian DSL (Domestic Substances List)

1-methoxy-2-propyl acetate (108-65-6)

Listed on the Canadian DSL (Domestic Substances List)

Solvent naphtha (petroleum), light aromatic (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

Octamethylcyclotetrasiloxane (556-67-2)

Listed on the Canadian DSL (Domestic Substances List)

Distillates (petroleum), hydrotreated middle (64742-46-7)

Listed on the Canadian DSL (Domestic Substances List)

silicon dioxide, amorphous (112945-52-5)

Listed on the Canadian DSL (Domestic Substances List)

Propane-1,2,3-triol (56-81-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

0075W-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Propane-1,2,3-triol (56-81-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information

: Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product