

### SECTION 1: Identification

#### 1.1. Identification

Product form	: Mixture
Trade name	: 1875-B
Product code	: 1875-B
Other means of identification	: 1875-B/1, 1875-B/5

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

Protective Industrial Polymers  
7875 Bliss Parkway  
North Ridgeville, Ohio 44039 - USA-Ohio  
T 440-327-0015  
[www.protectpoly.com](http://www.protectpoly.com)

#### 1.4. Emergency telephone number

Emergency number : Chemtrec: 800-427-9300 (Outside USA) 703-527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Acute toxicity (dermal) Category 4	H312	Harmful in contact with skin
Acute toxicity (inhalation:dust,mist) Category 4	H332	Harmful if inhaled
Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage
Germ cell mutagenicity Category 2	H341	Suspected of causing genetic defects
Specific target organ toxicity (single exposure) Category 2	H371	May cause damage to organs
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled  
H314 - Causes severe skin burns and eye damage  
H341 - Suspected of causing genetic defects  
H371 - May cause damage to organs  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P260 - Do not breathe vapors  
P261 - Avoid breathing vapors  
P264 - Wash hands, forearms and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product

# 1875-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective clothing  
P301+P312 - If swallowed: Call a doctor if symptoms persist. if you feel unwell  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
P302+P352 - If on skin: Wash with plenty of soap  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P310 - Immediately call a doctor if symptoms persist.  
P312 - Call a doctor if symptoms persist. if you feel unwell  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)  
P322 - Specific treatment (see ... on this label)  
P330 - Rinse mouth  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P363 - Wash contaminated clothing before reuse  
P405 - Store locked up  
P501 - Dispose of contents/container to in accordance with local regulations

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Phenol,4-nonyl-,branched	(CAS No) 84852-15-3	25 - 40	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Phenol	(CAS No) 108-95-2	5 - 15	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:dust,mist), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Muta. 2, H341 STOT SE 2, H371 STOT RE 2, H373 Aquatic Acute 3, H402 Aquatic Chronic 2, H411
Aliphatic Amine	(CAS No) Proprietary	< 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.  
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries after skin contact : Burns. May cause an allergic skin reaction.  
Symptoms/injuries after eye contact : Serious damage to eyes.  
Symptoms/injuries after ingestion : Burns.

# 1875-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Do not breathe vapors. Avoid contact with skin, eyes and clothing.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors. Use only outdoors or in a well-ventilated area. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Phenol,4-nonyl-,branched (84852-15-3)

Not applicable

#### Phenol (108-95-2)

Not applicable

#### Aliphatic Amine (Proprietary)

Not applicable

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

# 1875-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Hand protection:

Protective gloves

### Eye protection:

Safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Wear respiratory protection

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: light yellow
Odor	: mild
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No Data Available
Flash point	: Does Not Flash
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

# 1875-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin. Inhalation:dust,mist: Harmful if inhaled.

1875-B	
ATE US (oral)	549.4304037871 mg/kg body weight
ATE US (dermal)	1340.3416557162 mg/kg body weight
ATE US (dust, mist)	3.3333333333 mg/l/4h

Phenol,4-nonyl-,branched (84852-15-3)	
LD50 oral rat	1882 mg/kg (Rat; Other; Experimental value; 1412 mg/kg bodyweight; Rat; Experimental value)
ATE US (oral)	1882 mg/kg body weight
ATE US (dermal)	2040 mg/kg body weight

Phenol (108-95-2)	
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

Aliphatic Amine (Proprietary)	
LD50 oral rat	930 mg/kg
LD50 dermal rat	2000 mg/kg
LC50 inhalation rat (ppm)	3.89 ppm/1h
ATE US (oral)	930 mg/kg body weight
ATE US (dermal)	2000 mg/kg body weight
ATE US (gases)	1.945 ppmV/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : May cause damage to organs.

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Serious damage to eyes.

Symptoms/injuries after ingestion : Burns.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Phenol,4-nonyl-,branched (84852-15-3)	
EC50 Daphnia 2	0.085 mg/l (EC50; ASTM E729-88; 48 h; Daphnia magna; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 2	0.027 mg/l (EC50; EPA OTS 797.1050; 96 h; Skeletonema costatum; Static system; Salt water; Experimental value)

# 1875-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.2. Persistence and degradability

#### Phenol,4-nonyl-,branched (84852-15-3)

Persistence and degradability	Inherently biodegradable. Biodegradability in soil: no data available. Adsorbs into the soil. Photodegradation in the air.
-------------------------------	--

### 12.3. Bioaccumulative potential

#### Phenol,4-nonyl-,branched (84852-15-3)

BCF fish 1	271 (BCF; 480 h; Pimephales promelas)
BCF fish 2	1200/1300,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 32 days; Gasterosteus aculeatus; Flow-through system; Salt water; Experimental value; Fresh weight
Log Pow	3.28 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 5.4; Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

### 12.4. Mobility in soil

#### Phenol,4-nonyl-,branched (84852-15-3)

Log Koc	log Koc,Other; >= 4.35 - <= 5.69; Experimental value; GLP
---------	---

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.  
GWPmix comment : No known effects from this product.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3267 Corrosive liquid, basic, organic, n.o.s. (Aliphatic Amine, Nonyl Phenol), 8, II  
UN-No.(DOT) : UN3267  
Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s.  
Aliphatic Amine, Nonyl Phenol  
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136  
Packing group (DOT) : II - Medium Danger  
Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Symbols : G - Identifies PSN requiring a technical name

# 1875-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)  
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.  
TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 154
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids
- Emergency Response Guide (ERG) Number : 153
- Other information : No supplementary information available.

### TDG

#### Transport by sea

Not applicable

#### Air transport

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### 1875-B

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

# 1875-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

No additional information available

## SECTION 16: Other information

Other information : Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

Full text of H-phrases:

H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H371	May cause damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*