

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : AM-BLOCKFILL-B
 Product code : AM-BLOCKFILL-B
 Other means of identification : AM-BLOCKFILL-B/1, AM-BLOCKFILL-B/5, AM-BLOCKFILL-B/Q, AM-BLOCKFILL-B/HG

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Protective Industrial Polymers
 7875 Bliss Parkway
 North Ridgeville, Ohio 44039 - USA-Ohio
 T 440-327-0015
www.protectpoly.com

1.4. Emergency telephone number

Emergency number : Chemtrec: 800-427-9300 (Outside USA) 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral) H302
 Category 4
 Skin corrosion/irritation H314
 Category 1A
 Skin sensitization H317
 Category 1
 Specific target organ toxicity (repeated exposure) Category 1 H372
 Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Contains : 1-Piperazine ethanamine; 4-(2,4-dimethylheptan-3-yl)phenol; Phenol, 4-nonyl-, branched; Benzenemethanol; silicon dioxide, amorphous

Hazard statements (GHS-US) : H302 - Harmful if swallowed
 H314 - Causes severe skin burns and eye damage
 H317 - May cause an allergic skin reaction
 H372 - Causes damage to organs through prolonged or repeated exposure (oral)

Precautionary statements (GHS-US) : P260 - Do not breathe vapors
 P261 - Avoid breathing vapors
 P264 - Wash hands thoroughly after handling
 P270 - Do not eat, drink or smoke when using this product
 P272 - Contaminated work clothing must not be allowed out of the workplace
 P280 - Wear protective clothing
 P301+P312 - If swallowed: Call a doctor if you feel unwell
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
 P302+P352 - If on skin: Wash with plenty of soap
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

AM-BLOCKFILL-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a doctor if symptoms persist
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)
P330 - Rinse mouth
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container to in accordance with local regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
O,O'-Bis(2-aminopropyl)polypropyleneglycol	(CAS No) 9046-10-0	25 - 50	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
4-(2,4-dimethylheptan-3-yl)phenol	(CAS No) 25154-52-3	15 - 35	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Phenol,4-nonyl-,branched	(CAS No) 84852-15-3	20 - 30	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1-Piperazine ethanamine	(CAS No) 140-31-8	5 - 20	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1A, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
4-tert-butylphenol	(CAS No) 98-54-4	5 - 15	Skin Irrit. 2, H315 Eye Dam. 1, H318
Benzenemethanol	(CAS No) 100-51-6	0 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Burns. May cause an allergic skin reaction.
Symptoms/injuries after eye contact : Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

AM-BLOCKFILL-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam, water, water fog, CO2, dry chemical, dry sand, limestone powder.

5.2. Special hazards arising from the substance or mixture

Fire hazard : No data available on direct fire hazard.

Explosion hazard : No direct explosion hazard.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe vapors. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Incompatible products : Oxidizing agent. amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1-Piperazine ethanamine (140-31-8)

Not applicable

O,O'-Bis(2-aminopropyl)polypropyleneglycol (9046-10-0)

Not applicable

4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)

Not applicable

4-tert-butylphenol (98-54-4)

Not applicable

Phenol,4-nonyl-,branched (84852-15-3)

Not applicable

Benzenemethanol (100-51-6)

Not applicable

AM-BLOCKFILL-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colourless to light yellow
Odor	: Ammonical
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: ≈ 500 °F
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Solubility	: Water: Solubility in water of component(s) of the mixture : • : > 10 g/100ml (20 °C, soluble) • 4-tert-butylphenol: 0.06 g/100ml (25 °C, insoluble) • : 5.7 mg/l (25 °C, insoluble) • : 4.4 g/100ml (50 °C) • silicon dioxide, amorphous: 0.15 g/100ml • : 100 g/100ml (25 °C, Complete) • : > 10 g/100ml (20 °C, Complete)
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

----- TO BE COMPLETED -----

AM-BLOCKFILL-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. irritant gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

AM-BLOCKFILL-B	
ATE US (oral)	500.000 mg/kg body weight
1-Piperazine ethanamine (140-31-8)	
ATE US (oral)	1470.000 mg/kg body weight
ATE US (dermal)	880.000 mg/kg body weight
4-(2,4-dimethylheptan-3-yl)phenol (25154-52-3)	
ATE US (oral)	500.000 mg/kg body weight
4-tert-butylphenol (98-54-4)	
LD50 oral rat	> 2000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LC50 inhalation rat (mg/l)	> 5.6 mg/l/4h (Rat; Experimental value)
ATE US (oral)	3370.000 mg/kg body weight
ATE US (dermal)	2621.000 mg/kg body weight
Phenol,4-nonyl-,branched (84852-15-3)	
LD50 oral rat	1882 mg/kg (Rat; Other; Experimental value; 1412 mg/kg bodyweight; Rat; Experimental value)
ATE US (oral)	1882.000 mg/kg body weight
ATE US (dermal)	2040.000 mg/kg body weight
Benzenemethanol (100-51-6)	
LD50 oral rat	1620 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Inconclusive, insufficient data)
ATE US (oral)	1620.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
(Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (single exposure) : Not classified
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure (oral).

Aspiration hazard : Not classified
(Based on available data, the classification criteria are not met)

Symptoms/injuries after skin contact : Burns. May cause an allergic skin reaction.
Symptoms/injuries after eye contact : Serious damage to eyes.

AM-BLOCKFILL-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

1-Piperazine ethanamine (140-31-8)	
LC50 fish 1	> 100 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	58 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system)
Threshold limit algae 2	> 1000 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Fresh water)

4-tert-butylphenol (98-54-4)	
EC50 Daphnia 1	3.9 mg/l (EC50; 48 h)
LC50 fish 2	5.14 mg/l (LC50; 96 h)
Threshold limit algae 2	11.2 mg/l (EC50; 72 h)

Phenol,4-nonyl-,branched (84852-15-3)	
EC50 Daphnia 2	0.085 mg/l (EC50; ASTM E729-88; 48 h; Daphnia magna; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 2	0.027 mg/l (EC50; EPA OTS 797.1050; 96 h; Skeletonema costatum; Static system; Salt water; Experimental value)

Benzenemethanol (100-51-6)	
LC50 fish 1	460 mg/l (LC50; EPA OPP 72-1; 96 h; Pimephales promelas; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

AM-BLOCKFILL-B	
Persistence and degradability	Not established.

1-Piperazine ethanamine (140-31-8)	
Persistence and degradability	Not readily biodegradable in water. Low potential for mobility in soil.
Chemical oxygen demand (COD)	0.56 g O ₂ /g substance

4-tert-butylphenol (98-54-4)	
Persistence and degradability	Readily biodegradable in water. Low potential for mobility in soil. Photolysis in the air.
ThOD	2.77 g O ₂ /g substance

Phenol,4-nonyl-,branched (84852-15-3)	
Persistence and degradability	Inherently biodegradable. Biodegradability in soil: no data available. Adsorbs into the soil. Photodegradation in the air.

Benzenemethanol (100-51-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance

12.3. Bioaccumulative potential

1-Piperazine ethanamine (140-31-8)	
BCF fish 1	<= >0.3<=6.3,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; >4<=6 weeks; Cyprinus carpio; Flow-through system; Fresh water; Read-across
Log Pow	-1.48 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

4-tert-butylphenol (98-54-4)	
BCF fish 1	120 (BCF; 3 h)
BCF fish 2	20 - 88 (BCF)
BCF other aquatic organisms 1	34 (BCF; 24 h; Chlorella sp.)

AM-BLOCKFILL-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-tert-butylphenol (98-54-4)	
BCF other aquatic organisms 2	240 (BCF; 5 h; Bacteria)
Log Pow	3 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Phenol,4-nonyl-,branched (84852-15-3)	
BCF fish 1	271 (BCF; 480 h; Pimephales promelas)
BCF fish 2	1200/1300,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 32 days; Gasterosteus aculeatus; Flow-through system; Salt water; Experimental value; Fresh weight
Log Pow	3.28 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 5.4; Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).
Benzenemethanol (100-51-6)	
Log Pow	1-1.1,Experimental value; Other; 20 °C
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

1-Piperazine ethanamine (140-31-8)	
Log Koc	log Koc,4.57; Read-across; GLP
4-tert-butylphenol (98-54-4)	
Log Koc	log Koc,3.1; QSAR
Phenol,4-nonyl-,branched (84852-15-3)	
Log Koc	log Koc,Other; >= 4.35 - <= 5.69; Experimental value; GLP
Benzenemethanol (100-51-6)	
Surface tension	0.04 N/m (20 °C)

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contain and dispose of waste according to local regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s., 8, III

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

AM-BLOCKFILL-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672) T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : ----- TO BE COMPLETED/CALCULATED -----

Air transport

UN-No. (IATA) : ----- TO BE COMPLETED/CALCULATED -----

SECTION 15: Regulatory information

15.1. US Federal regulations

AM-BLOCKFILL-B

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

AM-BLOCKFILL-B

WHMIS Classification	Class E - Corrosive Material
----------------------	------------------------------

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

1-Piperazine ethanamine (140-31-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

AM-BLOCKFILL-B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

Other information

: Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product