

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : TLE-YELLOW-A
 Product code : TLE-YELLOW-A
 Other means of identification : TLE-YELLOW-A/1SF

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Protective Industrial Polymers
 7875 Bliss Parkway
 North Ridgeville, Ohio 44039 - USA-Ohio
 T 440-327-0015
www.protectpoly.com

1.4. Emergency telephone number

Emergency number : Chemtrec: 800427-9300 (Outside USA) 703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin corrosion/irritation, Category 2 H315
 Serious eye damage/eye irritation, Category 2A H319
 Sensitisation — Skin, Category 1 H317

Full text of H statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Contains :

(Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane)

Hazard statements (GHS-US) :

H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing vapours
 P264 - Wash hands thoroughly after handling
 P272 - Contaminated work clothing must not be allowed out of the workplace
 P280 - Wear protective clothing
 P302+P352 - If on skin: Wash with plenty of soap
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P321 - Specific treatment (see a doctor if symptoms do not go away. on this label)
 P332+P313 - If skin irritation occurs: Get medical advice/attention
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
 P337+P313 - If eye irritation persists: Get medical advice/attention
 P362+P364 - Take off contaminated clothing and wash it before reuse
 P363 - Wash contaminated clothing before reuse
 P501 - Dispose of contents/container to in accordance with local regulations

2.3. Other hazards

No additional information available

TLE-YELLOW-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
(Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane)	(CAS No) 25068-38-6	60 - 70	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Titanium Dioxide	(CAS No) 13463-67-7	15 - 20	Carc. 2, H351
Phenol,4-nonyl-,branched	(CAS No) 84852-15-3	0 - 3	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Dimethyl silicone polymer with silica	(CAS No) 67762-90-7	0 - 2	Not classified
Distillates (petroleum), hydrotreated middle	(CAS No) 64742-46-7	0 - 1	Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : When symptoms occur: go into open air and ventilate suspected area. Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact : When symptoms occur: rinse immediately with plenty of water. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Irritation of the eye tissue. Skin rash/inflammation.
- Symptoms/injuries after inhalation : May cause irritation or asthma-like symptoms. May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam, water, water fog, CO2, dry chemical, dry sand, limestone powder.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No data available on direct fire hazard.
- Reactivity : Polymerizes on exposure to some compounds e.g. amines, sulphurized compounds and (some) acids: release of heat.

5.3. Advice for firefighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

TLE-YELLOW-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Contain leaking substance. Dam up the liquid spill.
- Methods for cleaning up : Absorb spillage to prevent material damage. Cover the solid spill with dry sand/earth/vermiculite soda ash or powdered limestone.
- Other information : Dispose in a safe manner in accordance with local/national regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use. Keep only in original container. Store in a dry place. Store in a closed container.
- Storage area : Keep container in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

(Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane) (25068-38-6)

Not applicable

Distillates (petroleum), hydrotreated middle (64742-46-7)

Not applicable

Titanium Dioxide (13463-67-7)

ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (Titanium dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	LRT irr; A3
OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

Dimethyl silicone polymer with silica (67762-90-7)

Not applicable

Phenol,4-nonyl-,branched (84852-15-3)

Not applicable

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Personal protective equipment : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
- Hand protection : Gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Colour : Pigmented viscous liquid
- Odour : Light Musty to no odor
- Odour threshold : No data available

TLE-YELLOW-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: ≈ °F
Flash point	: ≈ 375 °F PMCC
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20 °C	: No data available
Density	: 9.5
Solubility	: Water: Solubility in water of component(s) of the mixture : • (Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane): mg/l (insoluble) 5.4-8.4 • Titanium Dioxide: 0.15 g/100ml • alpha-methyltoluene: 0.02 g/100ml • Xylenes: < 0.02 g/100ml • Phenol,4-nonyl-,branched: 5.7 mg/l (25 °C, insoluble)
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Polymerizes on exposure to some compounds e.g. amines, sulphurized compounds and (some) acids: release of heat.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Refer to Section 10 on Incompatible Materials.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. fume.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Dermal; Ingestion; Inhalation; Skin and eye contact

Acute toxicity : Not classified

(Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane) (25068-38-6)

LD50 oral rat	> 2000 mg/kg (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Titanium Dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value; > 5000 mg/kg bodyweight; Rat; Experimental value)
---------------	---

TLE-YELLOW-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium Dioxide (13463-67-7)	
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	> 6.8 mg/l/4h (Rat; Experimental value)

Phenol,4-nonyl-,branched (84852-15-3)	
LD50 oral rat	1882 mg/kg (Rat; Other; Experimental value; 1412 mg/kg bodyweight; Rat; Experimental value)
ATE US (oral)	1882.000 mg/kg bodyweight
ATE US (dermal)	2040.000 mg/kg bodyweight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Titanium Dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Symptoms/injuries after inhalation	: May cause irritation or asthma-like symptoms. May cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

TLE-YELLOW-A	
LC50 fish 1	3 mg/kg

(Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane) (25068-38-6)	
LC50 fish 2	2.3 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 2	1.1 - 2.8 mg/l (EC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

Titanium Dioxide (13463-67-7)	
EC50 Daphnia 1	> 100 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Weight of evidence)
Threshold limit algae 1	61 mg/l (EC50; Other; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

Phenol,4-nonyl-,branched (84852-15-3)	
EC50 Daphnia 2	0.085 mg/l (EC50; ASTM E729-88; 48 h; Daphnia magna; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 2	0.027 mg/l (EC50; EPA OTS 797.1050; 96 h; Skeletonema costatum; Static system; Salt water; Experimental value)

12.2. Persistence and degradability

(Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane) (25068-38-6)	
Persistence and degradability	Not readily biodegradable in water. Hydrolysis in water. Low potential for adsorption in soil.

Titanium Dioxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable. Low potential for mobility in soil.
Biochemical oxygen demand (BOD)	Not applicable

TLE-YELLOW-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium Dioxide (13463-67-7)	
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

Phenol,4-nonyl-,branched (84852-15-3)	
Persistence and degradability	Inherently biodegradable. Biodegradability in soil: no data available. Adsorbs into the soil. Photodegradation in the air.

12.3. Bioaccumulative potential

(Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane) (25068-38-6)	
BCF other aquatic organisms 1	3 - 31 (BCF)
Log Pow	>= 2.918 (Experimental value; EU Method A.8: Partition Coefficient; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Titanium Dioxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.

Phenol,4-nonyl-,branched (84852-15-3)	
BCF fish 1	271 (BCF; 480 h; Pimephales promelas)
BCF fish 2	1200/1300,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 32 days; Gasterosteus aculeatus; Flow-through system; Salt water; Experimental value; Fresh weight
Log Pow	3.28 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 5.4; Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 23 °C)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

12.4. Mobility in soil

(Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane) (25068-38-6)	
Surface tension	0.0 587-0.0589,20 °C
Log Koc	log Koc, SRC PCKOCWIN v2.0; 2.65; QSAR

Phenol,4-nonyl-,branched (84852-15-3)	
Log Koc	log Koc, Other; >= 4.35 - <= 5.69; Experimental value; GLP

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

No additional information available

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated for transport

TDG

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

TLE-YELLOW-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

Titanium Dioxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

Titanium Dioxide (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

Titanium Dioxide (13463-67-7)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Other information

: Disclaimer: This SDS to the best of our knowledge conforms to the requirements of OSHA 20 CFR 1910.1200 and summarizes the health and safety hazard information and general guidance on how to safely handle the material at the date of issue. Each user must review the SDS in the context of how the product will be handled and used in the workplace.

Full text of H-statements:

H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



TLE-YELLOW-A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

HMIS III Rating

- Health : 1 Slight Hazard - Irritation or minor reversible injury possible
- Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
- Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product